

A Probabilistic Quantitative Analysis of Probabilistic-Write/Copy-Select

Christel Baier¹, Benjamin Engel², Sascha Klüppelholz¹,
Steffen Märcker¹, Hendrik Tews², Marcus Völpl²

¹Institute for Theoretical Computer Science

²Operating-Systems Group

Technische Universität Dresden, Germany

NASA Formal Methods Symposium (NFM'13)
May 16, 2013

Motivation

Observation: traditional locking does not scale any more

- atomic operations are slow and become increasingly expensive
- locking schemes will become more complex and
- scalability becomes problematic on future hardware systems

Motivation

Observation: traditional locking does not scale any more

- atomic operations are slow and become increasingly expensive
- locking schemes will become more complex and
- scalability becomes problematic on future hardware systems

Idea: Probabilistic-Write/Copy-Select (PWCS) [Mc Guire'11]

- no locks, no atomic operations
- make inconsistencies detectable (e.g., tags, hashes)
- sufficiently high probability to find a consistent replica

Motivation

Observation: traditional locking does not scale any more

- atomic operations are slow and become increasingly expensive
- locking schemes will become more complex and
- scalability becomes problematic on future hardware systems

Idea: Probabilistic-Write/Copy-Select (PWCS) [Mc Guire'11]

- no locks, no atomic operations
- make inconsistencies detectable (e.g., tags, hashes)
- sufficiently high probability to find a consistent replica

Properties of PWCS

- measure-based experiments [Mc Guire'11]: promising approach
- promising to work with more relaxed memory models
- instance of a new class of algorithms (inherent randomness)

The PWCS protocol [Mc Guire'11]

Writer

```
for i=1..n
  r = replica[i];
  r.end_tag++;
  r.write_data();
  r.begin_tag++;
endfor
```

Replica

B_1	$Data_1$	E_1
B_2	$Data_2$	E_2
\vdots		
B_n	$Data_n$	E_n

Reader

```
for i=n..1
  r = replica[i];
  ta = r.begin_tag;
  r.copy_data();
  tb = r.end_tag;
  if (ta == tb)
    return data;
endfor

// error case
```


The PWCS protocol [Mc Guire'11]

Writer

```
for i=1..n
  r = replica[i];
  r.end_tag++;
  r.write_data();
  r.begin_tag++;
endfor
```

CTMC model

Replica



transition system
model

Reader

```
for i=n..1
  r = replica[i];
  ta = r.begin_tag;
  r.copy_data();
  tb = r.end_tag;
  if (ta == tb)
    return data;
endfor
```

// error case

CTMC model

Contribution (NFM'13)

- continuous-time Markov chain (CTMC) model for PWCS with multiple writers
- identify quantitative measures for the evaluation of PWCS
- formalization of quantitative measures in terms of continuous stochastic reward logic (CSRL)
- formal quantitative analysis of PWCS using the probabilistic model checker PRISM

Outline

- 1 Motivation
- 2 PWCS model**
- 3 PWCS properties
- 4 PWCS analysis
- 5 Conclusion and future work

Continuous-time Markov chain (CTMC)

Definition (CTMC)

A CTMC is a tuple $\mathcal{M} = \langle S, Act, R, \mu \rangle$, where

- S a finite state space,
- Act a finite set of action names,
- $R : S \times Act \times S \rightarrow \mathbb{R}_{\geq 0}$ the rate matrix of \mathcal{M} ,
- $\mu : S \rightarrow [0, 1]$ a distribution on S , i.e., $\sum_{s \in S} \mu(s) = 1$

Continuous-time Markov chain (CTMC)

Definition (CTMC)

A CTMC is a tuple $\mathcal{M} = \langle S, Act, R, \mu \rangle$, where

- S a finite state space,
- Act a finite set of action names,
- $R : S \times Act \times S \rightarrow \mathbb{R}_{\geq 0}$ the rate matrix of \mathcal{M} ,
- $\mu : S \rightarrow [0, 1]$ a distribution on S , i.e., $\sum_{s \in S} \mu(s) = 1$

Probability for $s \xrightarrow{\lambda:\alpha} s'$ ready to fire in $[0, t]$ is

$$1 - e^{-\lambda t}$$

Thus, the average delay of this transition is $1/\lambda$.

Continuous-time Markov chain (CTMC)

Definition (CTMC)

A CTMC is a tuple $\mathcal{M} = \langle S, Act, R, \mu \rangle$, where

- S a finite state space,
- Act a finite set of action names,
- $R : S \times Act \times S \rightarrow \mathbb{R}_{\geq 0}$ the rate matrix of \mathcal{M} ,
- $\mu : S \rightarrow [0, 1]$ a distribution on S , i.e., $\sum_{s \in S} \mu(s) = 1$

Probability for firing $s \xrightarrow{\lambda:\alpha} s'$ in $[0, t]$ is

$$P(s, \alpha, s') \cdot (1 - e^{-E(s) \cdot t})$$

where $E(s)$ denotes the exit rate of state s , i.e., the sum of the rates of all outgoing transitions of state s .

Continuous-time Markov chain (CTMC)

Definition (CTMC)

A CTMC is a tuple $\mathcal{M} = \langle S, Act, R, \mu \rangle$, where

- S a finite state space,
- Act a finite set of action names,
- $R : S \times Act \times S \rightarrow \mathbb{R}_{\geq 0}$ the rate matrix of \mathcal{M} ,
- $\mu : S \rightarrow [0, 1]$ a distribution on S , i.e., $\sum_{s \in S} \mu(s) = 1$

Probability for firing $s \xrightarrow{\lambda:\alpha} s'$ in $[0, t]$ is

$$\lambda / E(s) \cdot (1 - e^{-E(s) \cdot t})$$

where $E(s)$ denotes the exit rate of state s , i.e., the sum of the rates of all outgoing transitions of state s .

PWCS composed CTMC model

Product of CTMC for the **writers**, CTMC for the **readers**, and ordinary (non-stochastic) transition systems for the **replicas**.


$$\frac{s \xrightarrow{\lambda:\alpha} s'}{\langle s, \bar{x} \rangle \xrightarrow{\lambda:\alpha} \langle s', \bar{x} \rangle}$$

$$\frac{w \xrightarrow{\lambda:!a} w', \quad r \xrightarrow{?a} r'}{\langle w, r, \bar{y} \rangle \xrightarrow{\lambda:a} \langle w', r', \bar{y} \rangle}$$

\bar{x} : local states of all other components


\bar{y} : local states of all readers and remaining writers and replicas

PWCS model



Transition system model of a replica


PWCS model



CTMC model of a reader

PWCS model

CTMC model of a writer



Outline

- 1 Motivation
- 2 PWCS model
- 3 PWCS properties**
- 4 PWCS analysis
- 5 Conclusion and future work

Interesting quantitative measures

M1: probability to successfully read the data

Interesting quantitative measures

M1: probability to successfully read the data

M2: 99% time-quantile for successful reading

Interesting quantitative measures

M1: probability to successfully read the data

M2: 99% time-quantile for successful reading

Interesting quantitative measures

M1: probability to successfully read the data

M2: 99% time-quantile for successful reading

M3: fraction of time in which all replicas are damaged

M4: average time for repairing a damaged replica

M5: 99% time-quantile for repairing a damaged replica within time t

M6: probability to write at least c consistent replica within one write cycle

Interesting quantitative measures

M1: probability to successfully read the data

M2: 99% time-quantile for successful reading

M3: fraction of time in which all replicas are damaged

M4: average time for repairing a damaged replica

M5: 99% time-quantile for repairing a damaged replica within time t

M6: probability to write at least c consistent replica within one write cycle

... on the long run ...

Long-run behavior

Steady-state distribution

Function $\theta : S \rightarrow [0, 1]$ with

$$\theta(s) \stackrel{\text{def}}{=} \lim_{t \rightarrow \infty} \theta(s, t) \text{ with}$$

$\theta(s, t)$ the probability for being in state s at time $t \in \mathbb{R}_{\geq 0}$.

Long-run behavior

Steady-state distribution

Function $\theta : S \rightarrow [0, 1]$ with

$$\theta(s) \stackrel{\text{def}}{=} \lim_{t \rightarrow \infty} \theta(s, t) \text{ with}$$

$\theta(s, t)$ the probability for being in state s at time $t \in \mathbb{R}_{\geq 0}$.

Important:

θ is well-defined distribution on S for finite CTMCs.

Long-run behavior

Steady-state distribution

Function $\theta : S \rightarrow [0, 1]$ with

$$\theta(s) \stackrel{\text{def}}{=} \lim_{t \rightarrow \infty} \theta(s, t) \text{ with}$$

$\theta(s, t)$ the probability for being in state s at time $t \in \mathbb{R}_{\geq 0}$.

Important:

θ is well-defined distribution on S for finite CTMCs.

Long-run probabilities

Let $\mathcal{M} = \langle S, Act, R, \mu \rangle$ be a CTMC. We refer to the probability measure obtained for the CTMC

$$\mathcal{M}_\theta = \langle S, Act, R, \theta \rangle.$$

Conditional long-run behavior

Probability measure

Let $\mathcal{M} = \langle S, Act, R, \mu \rangle$ be a CTMC and $U \subseteq S$ be a set of states s.t. $\theta(U) > 0$. We refer to the probability measure obtained for the CTMC $\mathcal{M}_\theta^U = \mathcal{M}_\nu = \langle S, Act, R, \nu \rangle$

Conditional long-run behavior

Probability measure

Let $\mathcal{M} = \langle S, Act, R, \mu \rangle$ be a CTMC and $U \subseteq S$ be a set of states s.t. $\theta(U) > 0$. We refer to the probability measure obtained for the CTMC $\mathcal{M}_\theta^U = \mathcal{M}_\nu = \langle S, Act, R, \nu \rangle$, where

$$\nu(s) = \begin{cases} 0 & \text{if } s \in S \setminus U \\ \theta(s)/\theta(U) & \text{if } s \in U \end{cases}$$

Conditional long-run behavior

Probability measure

Let $\mathcal{M} = \langle S, Act, R, \mu \rangle$ be a CTMC and $U \subseteq S$ be a set of states s.t. $\theta(U) > 0$. We refer to the probability measure obtained for the CTMC $\mathcal{M}_\theta^U = \mathcal{M}_\nu = \langle S, Act, R, \nu \rangle$, where

$$\nu(s) = \begin{cases} 0 & \text{if } s \in S \setminus U \\ \theta(s)/\theta(U) & \text{if } s \in U \end{cases}$$

Conditional long-run queries

$\Pr(\Pi \mid U)$: conditional long-run probability

where Π is a measurable set of infinite paths, $U \subseteq S$ a set of states with $\theta(U) > 0$.

Conditional long-run behavior

Probability measure

Let $\mathcal{M} = \langle S, Act, R, \mu \rangle$ be a CTMC and $U \subseteq S$ be a set of states s.t. $\theta(U) > 0$. We refer to the probability measure obtained for the CTMC $\mathcal{M}_\theta^U = \mathcal{M}_\nu = \langle S, Act, R, \nu \rangle$, where

$$\nu(s) = \begin{cases} 0 & \text{if } s \in S \setminus U \\ \theta(s)/\theta(U) & \text{if } s \in U \end{cases}$$

Conditional long-run queries

$\Pr(\Pi \mid U)$: conditional long-run probability

$\text{AccRew}(\Diamond T \mid U)$: conditional long-run accumulated reward

where Π is a measurable set of infinite paths, $U \subseteq S$ a set of states with $\theta(U) > 0$. We assume $\Pr(\Diamond T \mid U) = 1$.

Queries for interesting long run properties

Q1: probability to successfully read a replica

$$\Pr(\neg error^j \ \mathcal{U} \ idle^j \mid reading_started_K^j)$$

Q2: time-quantile for successful reading within time bound t

$$\min\{t : p \leq \Pr(\neg error^j \ \mathcal{U}^{\leq t} \ idle^j \mid reading_started_K^j)\}$$

Queries for interesting long run properties

Q3: fraction of time in which all replicas are damaged

$$\theta(\text{damaged}_1 \wedge \dots \wedge \text{damaged}_K)$$

Queries for interesting long run properties

Q3: fraction of time in which all replicas are damaged

$$\theta(\text{damaged}_1 \wedge \dots \wedge \text{damaged}_K)$$

Q4: average time for repairing a damaged replica

$$\text{AccRew}(\Diamond \text{consistent}_k \mid \text{just_damaged}_k)$$

Queries for interesting long run properties

Q3: fraction of time in which all replicas are damaged

$$\theta(\text{damaged}_1 \wedge \dots \wedge \text{damaged}_K)$$

Q4: average time for repairing a damaged replica

$$\text{AccRew}(\diamond \text{consistent}_k \mid \text{just_damaged}_k)$$

Q5: time-quantile for repairing a damaged replica within time t

$$\min\{t : p \leq \Pr(\diamond^{\leq t} \text{consistent}_k \mid \text{just_damaged}_k)\}$$

Queries for interesting long run properties

Q3: fraction of time in which all replicas are damaged

$$\theta(\text{damaged}_1 \wedge \dots \wedge \text{damaged}_K)$$

Q4: average time for repairing a damaged replica

$$\text{AccRew}(\diamond \text{consistent}_k \mid \text{just_damaged}_k)$$

Q5: time-quantile for repairing a damaged replica within time t

$$\min\{t : p \leq \Pr(\diamond^{\leq t} \text{consistent}_k \mid \text{just_damaged}_k)\}$$

Q6: probability to write at least c replica within one cycle

$$\Pr(\Pi_c \mid \text{writing_started}_1^i)$$

Outline

- 1 Motivation
- 2 PWCS model
- 3 PWCS properties
- 4 PWCS analysis**
- 5 Conclusion and future work

Selected parameters and scenarios

Common parameters

	time	rate
write duration	2	$\lambda = 0.5$
read duration	1	$\delta = 1$
other	0.01	$\mu = \rho = \sigma = \nu = 100$

Selected parameters and scenarios

Common parameters

	time	rate
write duration	2	$\lambda = 0.5$
read duration	1	$\delta = 1$
other	0.01	$\mu = \rho = \sigma = \nu = 100$


Selected scenarios

	frequent reads moderate writes		moderate reads moderate writes	
	time	rate	time	rate
idle time (writer)	20	$\gamma = 0.05$	200	$\gamma = 0.005$
idle time (reader)	2	$\kappa = 0.5$	20	$\kappa = 0.05$

Results

Q1: probability to successfully read the data


moderate reads, moderate writes



Results


Q1: probability to successfully read the data

frequent reads, moderate writes



Results


Q2: time-quantile for successful reading
moderate reads, moderate writes, 5 replicas



Results


Q2: time-quantile for successful reading

frequent reads, moderate writes, 5 replicas



Results


Q3: time fraction in which all replicas are damaged
moderate reads, moderate writes



Results


Q3: time fraction in which all replicas are damaged

frequent reads, moderate writes




Results

Q5: time-quantile for repairing a damaged replica within time t
moderate reads, moderate writes, 5 replicas



Results

Q5: time-quantile for repairing a damaged replica within time t
frequent reads, moderate writes, 5 replicas



Outline

- 1 Motivation
- 2 PWCS model
- 3 PWCS properties
- 4 PWCS analysis
- 5 Conclusion and future work**

Conclusion and future work

Conclusion

- CTMC model for PWCS with multiple writers
- identification of quantitative measures for the evaluation of PWCS
- formalization of quantitative measures in terms of CSRL queries
- formal quantitative analysis of PWCS using PRISM

Conclusion and future work

Conclusion

- CTMC model for PWCS with multiple writers
- identification of quantitative measures for the evaluation of PWCS
- formalization of quantitative measures in terms of CSRL queries
- formal quantitative analysis of PWCS using PRISM

Future work

- comparative quantitative analysis with alternative protocols
- stronger object consistency in PWCS (e.g., multiple objects)
- other synchronization primitives (e.g., barriers)
- formal methods for quantile and (conditional) long run properties